UNDERWATER LED LIGHTS

SCR-24 Series

• 24 LEDs • 10,000 Lumens • 90W



DESCRIPTION

The SCR-24 underwater light provides your vessel 90 watts of intense LED lighting. The SCR-24's are designed within a compact 4" diameter bronze housing for under waterline thru-hull mounting. Single or multicolor version available with variable brightness and a wide array of control options.

FEATURES

- Proprietary clear-gel-filled design, injected through entire unit — eliminates condensation and/or water intrusion under stress
- Tough, scratch resistant, tempered glass lens with bronze housing — impervious to acetone, solvents and demanding marine environments
- Transient surge and reverse polarity protection dramatically prolongs unit life
- Thermal throttling technology enables safe operation even out of water
- From simple on-off to full-feature lighting effects, unit is enabled for a host of control interfaces
- Full color light "CC" has 12 built-in colors, and can be enabled with unlimited colors and many other advanced features using Shadow-NET®

3 CONTROL OPTIONS

1. Power Toggle Control

Quickly toggle power source to advance to next color or brightness level

2. Add Push Button Control

Connect to any push button controller Part # SCM-SWITCH-O-O-MOMENTARY

Ask about Shadow-Caster®'s highest quality, marine-grade push button controllers, optimized to work seamlessly with your lighting requirements.

3. Add Shadow-NET® Control

Dramatic, full-feature control through your Multifunction Display (MFD) by adding the Shadow-NET® control module (SCM-MFD-LC) & app

Push Button Modes

Single-Color Lights

- Light on
- Fade in /fade out
- Strobe

2-Color Lights

- Either single color on
- Fade between colors
- Strobe current color

Full Color Lights

- Any single color on
- Fade blue to white
- Fade through all 12 colors
- Strobe current color

Shadow-NET® Modes

- · Unlimited shades of color and fading
- Dimming Strobe rate Music sync
- · Multiple zones · And much more...

Dramatically enhanced lighting capabilities through your existing MFD


SPECIFICATIONS

- Up to 10,000 lumens
- 120 degree beam angle
- 90 watts power draw
- 7.8 amps operating current draw @ 12 volts
- 10-40 volts input
- 4" (102 mm) OD
- IP68 fully submersible waterproof design

INCLUDES

- · Lighting unit
- 10' (3 m) submersible-grade cable
- 3 Silicon bronze screws:
 #8 x 1½" L, square drive, FH
- Standard 2 year warranty





SCR-24 SERIES LIGHT COLOR MODELS	BIMINI BLUE	AQUA GREEN	GREAT WHITE	BIMINI BLUE / GREAT WHITE	FULL COLOR 12-color standard, or Unlimited colors with Shadow-NET®
MODEL #	SCR-24-BB-BZ-10	SCR-24-AG-BZ-10	SCR-24-GW-BZ-10	SCR-24-BW-BZ-10	SCR-24-CC-BZ-10
BADGE IDENTIFIER	SE	E E	SE	(SC	(SE